



Physical Characteristics:

Dimensions:

Fitting height: 86mm

- 400mm
- 600mm
- 800mm
- 1000mm

Diffuser Options:

Matt opal frosted

Mounting Options:

- Suspended 3 x wire 2000mm centred plus power flex
- Suspended 3 x wire 2000mm separate plus power flex
- Rod suspension (500mm)
- Surface mounted
- Flush

Canopy Size: 200mm Ø x 42mm H

Electrical Configuration:

Power:

- 400mm = 40 Watts
- 600mm = 60 Watts
- 800mm = 75 Watts
- 1000mm = 100 Watts

IP Rating:

IP20

Lumen Efficacy:

>107 Lumens / watt

LED Lifetime:

50,000 Hours @ 25°C

Control Gear:

Constant current LED Driver

Dimming Options:

Phase cut optional (400mm only)
SwitchDIM optional
DALI optional

Photometric's:

Lumen Output:

- 40 Watts = 4300 lumens
- 60 Watts = 6600 lumens
- 75 Watts = 8000 lumens
- 100 Watts = 10,700 lumens

LED Type:

LED boards

CRI:

CRI 80+

CCT:

3000k, 4000k, 5000k

(Outputs based on 4000k)

Distribution:

Direct. 120° Diffused.

(Indirect light is available)

Finishes:



Texture Black



Texture White



Tarnished Brass



Custom Colour
(Select your own)


Size options:




400mm



600mm




800mm




1000mm


Mounting options:



3 Wire Centred




3 Wire Separate



Rod Suspension



Surface Mounted



Flush

Discus pendants can be fitted with DALI control gear.