

contessalighting.com.au COPYRIGHT © 2021

# Dowel 40











# **Physical Characteristics:**

#### Profile:

40mm Diameter

#### Length:

Custom lengths up to 2.5 meters in powdercoat or 2.4m in premium finishes then a join or junction is required.

## Mounting:

See below - Suspension positions;

- 1 2m length = 200mm from each end
- 2.1 2.5m length = 300mm from each end Wire positions can be customised.

### Junctions:

Straight joins available.

# **Electrical Configuration:**

#### Power Options:

- 11 Watts / meter (Standard) 16 Watts / meter (High output)

#### IP Rating:

IP20 - For indoor use only. Should not be used in wet areas.

## Control gear:

24V Constant voltage LED Driver

# Dimming options:

- Phase cut included
- SwitchDIM optional
- DALI optional

# Photometrics:

#### Lumen packages:

- $11W = 1800 \, \text{Lm/m}$
- 16W = 2500 Lm/m

### LED type:

Tridonic LED flex light engine

#### CRI:

CRI 80 (CRI 90+ available)

#### CCT:

3000K or 4000K

## Distribution:

180° direct. Diffused

# Finishes:



Texture Black

Brushed Brass



Texture White



Tarnished Brass



Brushed Aluminium



Dark Bronze



# Mounting options:







