



Physical Characteristics:

Dimensions:

Profile: 100x100mm H

See diameters on next page

Diffuser Options:

Matt opal frosted

Mounting Options:

- Suspended 3 x wire 3000mm plus power flex back to canopy (BTC)
Canopy Size: 240mm Ø x 50mm H
- Suspended 3 x wire 3000mm plus power flex direct to ceiling (DTC)
Canopy size: 100mm Ø x 25mm H
Remotely stored driver

Electrical Configuration:

Power:

- 450mm = 30 Watts
- 600mm = 40 Watts
- 750mm = 62 Watts
- 900mm = 72 Watts
- 1200mm = 92 Watts

IP Rating:

IP20

Lumen Efficacy:

>80 Lumens / watt

LED Lifetime:

50,000 Hours @ 25°C

Control Gear:

Constant current LED Driver

Dimming Options:

Phase cut included (up to 600mm only)

1-10 Volt included (750mm +)

SwitchDIM optional

DALI optional

Photometric's:

Lumen Output:

- 30 Watts = 2715 lumens
- 40 Watts = 3620 lumens
- 62 Watts = 5456 lumens
- 72 Watts = 6336 lumens
- 92 Watts = 8096 lumens

LED Type:

Samsung LED boards

CRI:

CRI 80+

CCT:

3000k, 4000k, 5000k

(Outputs based on 3000k)

Distribution:

Direct. 120° Diffused.

Finishes:



Texture Black



Texture White



Tarnished Brass



Custom Colour
(Select your own)


Size options:




450 mm




600 mm



750 mm



900 mm



1200 mm

All pendants can be fitted with DALI control gear.