



Physical Characteristics:

Dimensions:

Profile: 100mm H

See diameters on next page

Diffuser Options:

Matt opal frosted

Mounting Options:

- Suspended 3 x wire 3000mm plus power flex back to canopy (BTC)

Canopy Size: 240mm Ø x 50mm H

- Suspended 3 x wire 3000mm plus power flex direct to ceiling (DTC)

Canopy size: 100mm Ø x 25mm H

Remotely stored driver

Electrical Configuration:

Power:

- 450mm = 40 Watts
- 600mm = 50 Watts
- 750mm = 72 Watts
- 900mm = 98 Watts
- 1200mm = 147 Watts

IP Rating:

IP20

Lumen Efficacy:

>100 Lumens / watt

LED Lifetime:

50,000 Hours @ 25°C

Control Gear:

Constant current LED Driver

Dimming Options:

1-10 Volt included

Phase cut optional (450mm only)

SwitchDIM optional

DALI optional

Photometric's:

Lumen Output:

- 40 Watts = 4021 lumens
- 50 Watts = 5011 lumens
- 72 Watts = 7456 lumens
- 98 Watts = 9898 lumens
- 147 Watts = 10,847 lumens

LED Type:

Samsung LED boards

CRI:

CRI 80+

CCT:

3000k, 4000k, 5000k

(Outputs based on 3000k)

Distribution:

Direct. 120° Diffused.

Finishes:



Texture Black



Texture White



Tarnished Brass



Custom Colour
(Select your own)


Size options:




450 mm




600 mm



750 mm



900 mm



1200 mm

All pendants can be fitted with DALI control gear.