



## Physical Characteristics:

### Dimensions:

Size: 30x90mm H

- 1200mm L
- 1800mm L
- 2400mm L
- Custom length (MOQ 10+)

### Diffuser:

PMMA - frosted

### Material:

Blackbutt hardwood

### Mounting Options:

- Suspended 2 x wire 2000mm (one acts as power supply) back to canopy (BTC)
  - Suspended 2 x wire 2000mm (one acts as power supply) direct to ceiling (DTC)
- No Canopy - remotely stored driver.

## Electrical Configuration:

### Power:

- 1200mm = 14 Watts
- 1800mm = 21 Watts
- 2400mm = 29 Watts

### IP Rating:

IP20

### Lumen Efficacy:

>143 Lumens / watt

### LED Lifetime:

50,000 Hours @ 25°C

### Control Gear:

24V Constant voltage LED Driver

### Dimming Options:

Phase cut included  
SwitchDIM optional  
DALI optional

## Photometric's:

### Lumen Output:

- 14 Watts = 1980 lumens /m
- 21 Watts = 3060 lumens /m
- 26 Watts = 4140 lumens /m

### LED Type:

Tridonic LED flex

### CRI:

CRI 80+ (CRI 90 available)

### CCT:

3000k, 4000k, 6500k

(Outputs based on 4000k)

### Distribution:

Direct - 100° Diffused.

## Finishes:



Blackbutt



Japan Black



White Wash