

Linear 70






LP-4570

Linear 70

Custom suspended linear luminaire for interior installation. Continuous lengths from 1000mm to 3000mm then join. Extruded aluminium body, recessed PMMA diffuser. Constant voltage remote driver required. Tridonic LLE flexible module.



Technical data

Profile:	W48mm x H70mm
Material:	Extruded aluminium + PMMA
IP Rating:	IP20
Light Source:	Tridonic LLE flexible module
	3000° K Warm white
Colour Temp:	4000° K Cool white Tunable white (MOQ 10+)
CRI:	CRI80+ (90+ available)
Beam Angle:	110° Direct
Dimming:	Phase-cut (included) SwitchDIM DALI Casambi
Driver:	24V constant voltage
Suspension:	2-in-1 Suspension cables
Warranty:	3 Years (only applies to electrics)
Leadtime:	1-3 Weeks


Length (mm)	Output
1200	1560
1500	1960
1800	2350
2000	2600
2400	3130
2700	3520
3000	3900
Custom	1300 lms/m

Finish options


 Texture Black	 Texture White	 Texture Silver	 Brushed Brass (Up to 2100mm)
 Gold Pearl	 Copper Bronze	 Dark Bronze	 Custom Finish

Mounting options


M1 - Bullets




M2 - Canopies




M3 - Rods




M4 - Centre Linear Canopy (450x65x41mmH)



M5 - Side Linear Canopy (240x65x41mmH)




M6 - Surface Mounted



Canopy options (For option M2 above)


RC38

(32mm cut-out)




RC70


(51mm cut-out)



SC70



SC100



Linear 70 code generator

Product Code	Length		Finish		Output		Colour Temp		Mounting		Canopies (for M2)		Driver	
	1200mm	120	Texture Black	TB	High Output	HO	3000K	3K	Bullets	M1	RC38	R38	Phase Cut	PC
	1500mm	150	Texture White	TW	Custom	xx	4000K	4K	Canopies	M2	RC70	R70	SwitchDim	SwD
	1800mm	180	Texture Silver	TS					Rods	M3	SC70	S70	DALI	DA
	2000mm	200	Gold Pearl	GP					Centre Canopy	M4	SC100	S100	Casambi	CAS
	2400mm	240	Brushed Brass	BB					Side Canopy	M5	(Leave blank if not required)			
	2700mm	270	Copper Bronze	CB					Surface Mount	M6				
	3000mm	300	Dark Bronze	DB										
	Custom	xxx	Custom	xx										

LP-4570	—	—	—	HO	—	—	—	—
---------	---	---	---	----	---	---	---	---

(Example: LP-4570-150-TB-HO-4K-M2-R70-PC)

Suspension placement

Suspension mounts can be specified anywhere along the length of the linear. If the mounting centres are not specified the standard is:

<2000mm length = 200mm from each end
2100 - 3000mm length = 300mm from each end

If custom placement is required, please specify the required placement before ordering.

Suspension lengths

The standard suspension lengths are as per the below:

Wire = 2000mm
Rods = Up to 1200mm continuous then join

If custom suspension length is required, please specify the required length before ordering.

Canopy finishes

All canopies are available in the following finishes:

Texture Black
Texture White
Texture Silver
Gold Pearl
Copper Bronze
Dark Bronze

If a canopy finish is not specified, Texture White will be supplied as standard.