



Everglade





PHYSICAL CHARACTERISTICS:

DESCRIPTION

The Everglade is a pendant light that features an in-direct inner facing light source with an evergreen biophilic inspired moss panel that sits in the centre of the light ring.

DIAMETERS

50mm
0mm
0mm
00mm
00mm
00mm

DIFFUSER

PMMA

Texture BlackTexture WhiteBrushed GoldGold PearlCopper BronzeDark BronzeTexture Silver

FRAME FINISHES: (Powder coated - all diameters)

Custom Powder Coast Finish: Please specify,

40



ELECTRICAL CONFIGURATION:

TRIDONIC FLEX LIGHT ENGINE (Constant Voltage)

HO 28W = 2800 Lms
HO 38W = 3800 Lms
HO 50W = 5000 Lms
HO 62W = 6200 Lms
HO 74W = 7400 Lms
HO 94W = 9400 Lms

CCT

- 3000K Warm White (Stocked) 4000K Cool White (Stocked)
- 5000K Day Light
- RGB (Different wattage applies)
- RGBW (Different wattage applies)

CRI

CRI >80 (Standard)
CRI 90+

IP RATING

IP20 (For indoor use only. Should not be used in wet areas)

DIMMING

PROFILE SIZE:



CONTROL GEAR

Tridonic constant voltage non dimmable Contessa constant voltahe triac dimmable Tridonic One4All DALI constant voltage driver

WARRANTY

3 Years (standard)

5 Years (optional - fees apply)



Everglade

SIZE DIAGRAMS:



- 240 —



Everglade

Code Generator:

Product	Diameter	Finish	Output	ССТ	Mounting	Driver
EVERGLADE	450MM - 45	Texture Black - BL	High Efficiency - HE	3000к - 3к	Direct to Ceiling - DTC	On/Off - OFF
	600MM - 60	Texture White - WH	High Output - HO	4000к - 4к	Back to Canopy - BTC	Phase Cut- PC
	800MM - 80	Gold Pearl - GP		6500K - 5K		DALI - DA
	1000MM - 100	Copper Bronze - CB		RGB - RGB		SwitchDIM- SwD
	1200MM - 120	Dark Bronze - DB		RGBW - RGBW		Casambi - CAS
	1500MM - 150	Texture Silver - TS				
		Brushed Gold BG				
		CUSTOM - CF				
EVG		-				-

When specifying custom details e.g. finish, please include the details in the comments section of the online project quote request function on our website or include in the lighting schedule.