


contessalighting.com.au COPYRIGHT © 2024







TRIDONIC FLEX LIGHT ENGINES







PHYSICAL CHARACTERISTICS:										
DESCRIPTION	FRAME FINISHES:	TIMBER CAP FINISHES:								
The Dowel 43T is an Australian Made aluminium linear light that features tasmanian oak timber ends. The pendant is available in custom lengths and includes Tridonic LED flexible modules.	Texture Black	Tasmanian Oak								
Length	Texture White	Black Japan								
1200mm	Gold Pearl	French White Wash								
1500mm Length is the total length (including timber ends) e.g 1200mm = 900mm light bar + 150mm timber end x 2	Copper Bronze	PROFILE SIZE:								
2400mm 2700mm	Dark Bronze									
3000mm Custom length	Texture Silver									
For custom lengths, LED Flex Module - 100mm increments.	Custom Finish Please specify,	43								
DIFFUSER										
Polycarbonate - Gloss Opal	Custom finishes you can specify are Dulux powder coats. Contact us for more information.									
		18								
ELECTRICAL CONFIGURATION:										
TRIDONIC FLEX LIGHT ENGINE (Constant Voltage)	сст	DIMMING								
10 W/m = 1200 Lms/m (LO)	3000K Warm White (Stocked)	On/Off								
14 W/m = 1800 Lms/m (HE) (Stocked)	4000K Cool White (Stocked)	Phase Cut (Standard)								
20 W/m = 2500 Lms/m (HO) (Stocked)	5000K Day Light	SwitchDIM								
		DALI								
DISTRIBUTION	CRI	Casambi								
Direct light only. 100° Diffused.	CRI >80 (Standard)	CONTROL GEAR								
COLOUR TOLERANCE	CRI 90+	Tridonic constant voltage non dimmable								
3 SDCM		Contessa constant voltage triac dimmable								
O ODOW	IP RATING	Tridonic One4All DALI constant voltage driver								
TEMPERATURE TOLERANCE	IP20 (For indoor use only. Should not be used in	WARRANTY								

MacAdam 3

solder joins)

LED MANUFACTURER


Made in Europe by Tridonic / reel2reel (no

wet areas)


3 Years (standard)
5 Years (optional - fees apply)

MOUNTING OPTIONS:


Option 1 - Suspended with Bullets (standard)




Option 2 - Suspended with Canopies (RD)




Option 3 - Suspended with Rods



Option 4 - Suspended with Centre Canopy



Option 5 - Suspended with Side Canopy



SUSPENSION PLACEMENT

Suspension mounts can be specified anywhere along the length of the linear however the standard is;

1500 & 1800mm long = 150mm in from each end 2400mm long = 250mm in from each end

Custom placement Please specify,

SUSPENSION LENGTH

Suspension lengths can be specified longer however the standard is;

Wires = 2000mm long (adjustable)

Rod = 1500mm continuous before join


Custom length Please specify,

CANOPY OPTIONS: (For option 2 & 3 above)









100mm Surface

100



CANOPY FINISHES

All canopies are avaiable in White or Black.


Timber Canopies are not available.








Side Mount Canopy (For option 5 above)



Centre Mount Canopy (For option 4 above)







Code Generator:

Product	Length	Frame Finish	Timber Caps	Output (10W/m Not Stocked)	CCT (65K Not Stocked)	Mounting	Canopies (If selected M2 or M3)	Driver
DOWEL 43T	1200MM - 120	Texture - TB	Tas / Oak - TO	10W 1200 - LO Lms/m	3000К - 3К	Option 1 - M1	Recess 38mm - R38	On/Off - OFF
	1500MM - 150	Texture White - TW	Japan Black - JB	14W 1800 - HE Lms/m	4000К - 4К	Option 2 - M2	Recess 70mm - R70	Phase Cut-PC
	1800MM - 180	Texture - TS	White Wash - FWW	20W 2500 Lms/m - HO	6500K - 65K	Option 3 - M3	Surface 70mm - s70	DALI - DA
	2000MM - 200	Gold Pearl- GP				Option 4 - M4	Surface 100mm - s100	SwitchDIM- SwD
	2400MM - 240	Copper Bronze - CB				Option 5 - M5		Casambi - CAS
	2700MM - 270	Dark Bronze - DB						
	3000MM - 300	CUSTOM - C/F						
	CUSTOM - C/L							
LP-43DWT	-	-	-		_		-	

When specifying custom details e.g. finish, please include the details in the comments section of the online project quote request function on our website or include in the lighting schedule.